

FOR POOLS  
**45 to 115m<sup>3</sup>**

OPERATES DOWN  
to **-10°C**

**3 versions**  
available

**POOLEX**  
FOLLOW THE EXPERT  
**POOLEX PLATINIUM**

**Jetline  
PLATINIUM**



## POOLEX PLATINIUM

### Design, concept, and performance

- Vertical high range design
- Ultra-silent Full Inverter technology
- Brushed aluminium shell
- Operates down to -10°C

**LED**  
Indicative Technology



#### Smart ambient LED

Exclusive LED technology to know the status of your heat pump at a glance.

- Blue = Your pool is being heated
- Green = Your heat pump has reached setpoint temperature
- Red = Heat pump inactive

	90	120	155
Pool volume	45 to 65 m <sup>3</sup>	65 to 85 m <sup>3</sup>	80 to 115 m <sup>3</sup>
COP air 15°C/water 26°C	7.3 ~ 4.83	7.3 ~ 4.8	6.8 ~ 4.57
Noise level at 10m (db(a))	<29 ~ <21	<31 ~ <23	<32 ~ <24

**HEAT PUMP ONSITE\* WARRANTY**

**3  
YEARS**

**COMPRESSOR WARRANTY**

**7  
YEARS**

**TITANIUM COIL  
CORROSION WARRANTY**

**15  
YEARS**



POOLEX PLATINIUM		90	120	155
Swimming Pool volume		45 to 65m <sup>3</sup>	65 to 85 m <sup>3</sup>	80 to 115 m <sup>3</sup>
Reference: PC-PTM		090	120	155
Air 26°C Water 26°C Hygro 80%	Max. power output (kW)	12.2	15.1	20.93
	Min. power output (kW)	2.78	4.7	5.23
	Power consumption (kW)	1.79 ~ 0.2	2.22 ~ 0.26	3.22 ~ 0.46
	COP	13.3 - 6.8	13.3 ~ 6.8	11.37 ~ 6.5
Air 15°C Water 26°C Hygro 70%	Max. power output(kW)	9.03	12.1	15.5
	Min. power output (kW)	2.09	2.8	3.88
	Power consumption (kW)	1.86 ~ 0.28	2.5 ~ 0.4	3.39 ~ 0.57
	COP	7.3 ~ 4.83	7.3 ~ 4.8	6.8 ~ 4.57
Electricity supply		MONO 230V / 50Hz		
Max. current(A)		16	20	21.86
Heating temperature range		15°C / 40°C		
Operating range		-10°C / 43°C		
Flow (m <sup>3</sup> /h)		3.3	4.4	6.7
Refrigerant		R32		
Packaging dimensions (mm)		Ø1 040x1010		
Dimensions (mm)		Ø935x845		
Net/gross weight (kg)		59 / 67	65 / 73	75 / 83
Noise level at 1 m (dB(A))		<48 ~ <40	<49 ~ <41	<52 ~ <42
<b>Noise level at 10 m (dB(A))</b>		<b>&lt;29 ~ &lt;21</b>	<b>&lt;31 ~ &lt;23</b>	<b>&lt;32 ~ &lt;24</b>
Compressor type		ROTATION		
<b>Compressor brand</b>		<b>MITSUBISHI</b>		
Heat exchanger		Titanium Twisted Tech®		
Function		EcoBooster & EcoSilence (inverter) / Heating / Cooling		
Load losses (mCE)		1.1	1.1	1.1

STANDARD E.U. CERTIFIE T.U.V.  
Informations données à titre indicatif et susceptibles d'être modifiées sans préavis

**Because, we, at Poolex, do not believe in compromising striking design over performance, we have created the Poolex Platinum.**

*Poolex finally offers users a solution to their concern: how to efficiently hide one's heat pump? And if it was instead openly featured?*

Its modern design includes the latest Full Inverter technology with a guaranteed COP over 7 and absolute silence at less than 21db at 10m. As it is the case for the whole Poolex range, the Platinum also features the new, more eco-friendly and efficient R32 refrigerant.

Choose instantly and with a simple touch one of the three operating modes (INVERTER / ECO SILENCE / CRUISE).

**Worldwide Innovation:** Integrated ambient LED indicate at a glance the status of your heat pump: **Blue:** Your pool is being heated. **Green:** Your heat pump has reached setpoint temperature. **Red:** Heat pump inactive.

**Warranty:** Poolex has increased its warranty on the entire Premium range to 7 years.

## The POOLEX Advantage: accessories included



Delivered on wooden pallet



Thermal winter storage cover



Anti-vibration support kit



PVC Connectors  
Ø 50mm 1" 1/2



Condensation drainage pipe



Maintenance kit including multi-language user manual